Sky Arrow KIT Equipment & Options			
Notes	Description	Experimental MA010	
	AIRFRAME & CONTROLS	III/IOIO	
	Weather-resistant white finish	٧	
	Clear canopy with air Vents, Sliding Side Window & Lock	V	
	Clear removable aft windows	√	
	Non-skid floor w/ Map/Glove compartment box	V	
	Adjustable front rudder pedals	V	
	Seat cushions	V	
	Cabin heating, ventilation & canopy demisting system	•	
	Seat belts & shoulder harness, five points, dual	√	
	Canopy release system	•	
	Baggage containers (behind & under the rear seat)	•	
	Map box under front seat	V	
	112 It wing fuel tank	٧	
	Engine firewall	٧	
	First aid kit	•	
	Fire extinguisher	•	
	Electric pitch trim	V	
	Hand-operated brakes	V	
	AUXILIARY ACCESSORIES		
	Fuel Level Measuring Stick	V	
	Fuel Inspection Cup	V	
	Fuel Funnel with Filter	•	
	Yaw Gust Control Lock	٧	
	2 aileron padded locks, w/ "Remove Before Flight" Streamer	V	
	Pitot tube & static port plug, w/ "Remove Before Flight" Streamer	V	
	Stall Warning port plug, w/ "Remove Before Flight" Streamer	V	
	POWERPLANT	,	
	Engine: Rotax 912ULS 98hp (73,5 KW) @5.800 rpm	٧	
	Sliding clutch and improved electrical starter	٧	
	3 blade on ground adjustrable pitch carbon fiber propeller	V	
	Taxiing cooling fans	V	
	Adjustable cooling system for engine coolant and oil	V	
	Additional 40 Amp alternator	•	
	Vacuum Pump	•	
	Carburetor airbox	V	
	Propeller spinner	V	
	Carburetor Heating System	V	
	ENGINE INSTRUMENTATION	- 4	
	Tachometer	V	
	Fuel Quantity Indicator	V	
	Fuel Pressure Indicator & alarm indicator	V	
	Oil Pressure Indicator	٧	
	Oil Temperature Indicator	V	
	Cylinder Head Temperature Indicator	٧	
	Vacuum gauge	•	
	Volt / Ampere indicator with alarm led	V	
	PILOT WARNINGS		
	Landing light ON - blue lamp	•	
	Low Oil Pressure - Red Lamp	V	

I	High Oil Temperature - Red Lamp	V
	CHT - Red Lamp	V
	Auxiliary engine and instrument panel fans ON - Blue Lamp	V
	Fuel Low - Amber Lamp	· ·
		٧
	Voltage Regulator - Red Lamp	V
	Push to Test button (Warning Lights)	V
	FLIGHT INSTRUMENTATION	-1
	Magnetic Compass	V
	Airspeed Indicator	V
	Altimeter	٧
	Altitude encoder	•
	Vertical Speed Indicator	٧
	Attitude Indicator (pneumatic)	•
	Directional Gyro (pneumatic)	•
	Turn and bank indicator (electric) & Sideslip Indicator	•
	Flaps position Indicator	•
	Pitch Trim Position Indicator	٧
	Outside air temperature (OAT) indicator	•
	Digital chronometer	٧
	Stall Warning System (acoustic)	٧
	Flight Hour Meter	V
	Landing light	•
	Navigation & strobe lights	•
	Instrument post light w/ dimmer control	•
	Map light AVIONICS PRE ARRANGEMENTS & WIRING	•
	Vacuum subsystem w/ Suction indicator	•
	19 Ah power battery	V
	COM Antenna	•
	Transponder Antenna	•
	VOR Antenna	•
	Breakers & Switches	٧
	AVIONICS	
I	NAV / COM Bendix King KX-125	•
	NAV / COM Bendix King KX-155 w/ CDI/VOR/GS indicator Bendix King KI-204 (replaces I)	•
II	Bendix King KT 76A (Mode C transponder)	•
	Garmin GTX 327 (Mode C transponder, replaces II)	•
	GPS/NAV/COM Garmin GNS 430 and CDI/VOR/GS indicator Garmin GI-106A (replaces I)	•
	Intercom Sigtronics SPA 400	٧
	Headsets for two	•
	Emergency Locator Transmitter MISCELLANEOUS	•
	External power jack	•
	Nose Wheel mud guard & Main Wheel fairings	•
		•
III	Nose Wheel mud guard & Main Wheel fairings	•
III	Nose Wheel mud guard & Main Wheel fairings Toe brakes (upgrade)	•
III	Nose Wheel mud guard & Main Wheel fairings Toe brakes (upgrade) Rack for wing and horizontal tail transportation Trailer for aircraft on road transportation (requires III) Set of stakes and ropes for aircraft tie down	•
III	Nose Wheel mud guard & Main Wheel fairings Toe brakes (upgrade) Rack for wing and horizontal tail transportation Trailer for aircraft on road transportation (requires III) Set of stakes and ropes for aircraft tie down Disabled pilot controls	•
III	Nose Wheel mud guard & Main Wheel fairings Toe brakes (upgrade) Rack for wing and horizontal tail transportation Trailer for aircraft on road transportation (requires III) Set of stakes and ropes for aircraft tie down	•

- Not available on the configuration
 Available as optional on the configuration
 V Standard item included in the configuration